

Product Information

ISO Class 3-5

Cleanroom Class 1 - 100 EU Grade B/C/D

PureSorb™ Foam Wiper

Laundered open-cell polyurethane foam wiper

PureSorb[™] foam wipers are made of 100 ppi polyester-based hydrophilic polyurethane foam. The foam is reticulated in a thermal process to create the open cell structure, significantly increasing the sorbency and improving the entrapment and

removal of particles during wiping applications. The wipers and non-abrasive properties of PureSorb™ Foam Wipers are precision cut by laser and laundered, to reduce the fibers and particles to an extremely low level. The combiand above environments. nation of the excellent sorbency, low fibers and the soft

result in the superior performance required in ISO Class 3



Key Attributes

- Polyester-based polyurethane foam wiper
- 100 ppi open cell hydrophilic foam
- Reticulated in a non-chemical process
- Laser cut edge


Benefits

- Critically low fibers and particles
- Chemically compatible with IPA and other solvents
- High sorbency capacity
- Soft and non-abrasive
- Entraps and removes the particles
- Easy Open Notch
- Autoclavable

- Light weight, high sorbency design reduces landfill waste impact when compared to more traditional heavier weight designs
- Complies with RoHS and REACH requirements



- Screen cleaning in microelectronics
- Cleaning in pharmaceutical and medical device manufacturing
- Enhanced removal of disinfecting solutions
- Padded work surface
- Digital printing for cleaning solvents and inks
- Cellulose sponge replacement
- Excellent for applying cleaning solutions to large surfaces
- Wiping down glass vessels



www.berkshire.eu.com

Contact: Tel 44 (0) 870 757 2877 enquiries@

BIL_1056_09

berkshire.uk.com	Euro
	SE A
-2015	lana

America	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
Japan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@berkshire.co.jp



Technical Data:

Attribute		Units	Value	Test Method
Basis Weight		g/m²	116	TAPPI T-410
Caliper		Inch	0.15	ASTM D-1777
Fibers	≥100µm	fibers/cm ²	0.034	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.2
Particles	≥ 0.5 µm	x10 ³ /cm ²	0.38	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.1
Sorbency	Capacity	mL/m²	1200	IEST-RP.CC004.3, Sec 8.1 modified / Sec 8.2 modified
	Efficiency	mL/g	10	
Non-Volatile Residue	DI Water	g/m²	0.089	IEST-RP.CC004.3, Sec 7.1.2
	IPA	_g/m²	1.1	
Ions	Na ⁺	ppm	9.1	IEST-RP.CC004.3, Sec 7.2.2
	K ⁺	ppm	0.022	
	Ca++	ppm	0.00057	
	Mg ⁺⁺	ppm	0.00042	
	CI-	ppm	1.6	

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- Third party testing can be performed upon request

Order Information:

Product	Number	Size	Thickness	Shts/pk	Pks/cs	Style
PureSorb™	PS040520	4x5" (10x13cm)	0.15" (0.38cm)	50	20	Stacked
PureSorb™	PS06098	6x9" (15x23cm)	0.15" (0.38cm)	50	8	Stacked

Other Berkshire Products



Wipers



Glove Liners



Mop Systems



Documentation Systems



Face Masks



Swabs

www.berkshire.eu.com

Contact: Tel 44 (0) 870 757 2877/ enquiries@berkshire.uk.com